



US008154200B2

(12) **United States Patent**
Hunze et al.

(10) **Patent No.:** **US 8,154,200 B2**
(45) **Date of Patent:** **Apr. 10, 2012**

(54) **ENCAPSULATION OF ORGANIC DEVICES**

(75) Inventors: **Arvid Hunze**, Erlangen (DE); **Debora Henseler**, Erlangen (DE); **Karsten Heuser**, Erlangen (DE)

(73) Assignee: **OSRAM Opto Semiconductors GmbH**, Regensburg (DE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 226 days.

(21) Appl. No.: **12/290,708**

(22) Filed: **Nov. 3, 2008**

(65) **Prior Publication Data**

US 2009/0066240 A1 Mar. 12, 2009

Related U.S. Application Data

(63) Continuation of application No. 11/141,476, filed on May 31, 2005, now abandoned.

(60) Provisional application No. 60/627,905, filed on Nov. 15, 2004.

(51) **Int. Cl.**
H05B 33/04 (2006.01)

(52) **U.S. Cl.** **313/512**; 445/25; 313/504

(58) **Field of Classification Search** 313/504,
313/509, 512; 445/25; 257/40; 438/39,
438/127

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,737,625 A 6/1973 Martin
5,843,265 A 12/1998 Grimm
6,692,610 B2 2/2004 Low et al.

6,696,312 B2 2/2004 Guenther et al.
6,699,728 B2 * 3/2004 Guenther et al. 438/39
6,784,009 B2 8/2004 Lim et al.
6,803,245 B2 10/2004 Auch et al.
6,936,963 B2 * 8/2005 Langer et al. 313/509
6,998,776 B2 2/2006 Aitken et al.
7,144,471 B2 12/2006 Kobayashi et al.
7,365,442 B2 4/2008 Pichler
2002/0108707 A1 8/2002 Kobayashi et al.
2003/0062518 A1 * 4/2003 Auch et al. 257/40

(Continued)

FOREIGN PATENT DOCUMENTS

WO WO 01/44865 6/2001
WO WO 01/45140 6/2001

OTHER PUBLICATIONS

The American Heritage Dictionary, Fourth Edition, 2004, Houghton Mifflin Company, p. 536.

Primary Examiner — Nimeshkumar Patel

Assistant Examiner — Mary Ellen Bowman

(74) *Attorney, Agent, or Firm* — Cozen O'Connor

(57) **ABSTRACT**

Presented an organic light-emitting device (OLED) that includes at least one active region, at least one organic layer, a first glass plate on which the at least one active region is applied, and a second glass plate. The active region is disposed between the first and the second glass plates. The first and second glass plates are at least partially transparent in the near infrared spectral range. The OLED further includes a bonding material that includes a solder glass and is disposed between the first and second glass plates. The bonding material forms at least one frame that surrounds the active region and mechanically connects the first glass plate with the second glass plate and seals the active region. The bonding material absorbs near infrared radiation. The OLED further includes spacer particles that have a mean diameter that maintains a height between the first and second glass plates.

12 Claims, 5 Drawing Sheets

